













 Darstellung  
 Image **80%**

	Anschlagprofil, Aluminium Stop profile	6000 mm	<b>12226</b>
	Glashalteprofil, Aluminium Glass holding profile	6000 mm Bohrabstand Bore distance 150 mm	<b>12223</b>
	Schraube M6 x 10 DIN 913 Screw M6 x 10 DIN 913	VPE 25 PU 25	<b>SC003</b>
	Klemmprofil, Aluminium Clamping profile	6000 mm	<b>12224</b>
	Einstellprofil, Aluminium Adjustment profile	6000 mm	<b>12227</b>

Kippbeschlag<sup>®</sup>  
 Tilting armature<sup>®</sup>

# 226

	Einfassprofil, Weich-PVC transparent Bordering profile, Soft-PVC transparent	8 mm Glas/glass	<b>22413</b>
	Dichtungsgummi, EPDM schwarz Sealing rubber, EPDM black		<b>22004</b>
	Abdeckprofil, PVC Covering profile, PVC	6000 mm	<b>30160</b>
	Rundschnur, Weich-PVC Cord, Soft-PVC	4 mm	<b>00535</b>
 2 x M4 x 16 DIN 7985 2 x M3 x 6 DIN 965	Arretierung Locking mechanism		<b>22403</b>
	Stellschraube, Edelstahl Adjusting screw, stainless steel	M6	<b>22401</b>
rechts/right	Endkappe, Aluminium End cap	rechts/right	<b>24079</b>
 2 x M3 x 10 DIN 7500-M		links/left	<b>24080</b>
 2 x Ø 2,5	Bohrschablone – Glashalteprofil für Arretierung 22403 Drilling jig – glass holding profile for locking mechanism 22403		<b>23483</b>